

RESIDENTIAL INSPECTION REQUEST FORM
(Smoke Alarm, Carbon Monoxide Alarm, Fire Extinguisher Compliance)

Bureau of Fire Prevention, 1203 Paterson Plank Road, Municipal Government Center, Secaucus, NJ 07094

Date: _____

Property Location: _____

Homeowner's Name: _____ Phone #: _____

Address: _____

Sale Buyer's Name _____ Phone # _____

Rental Tenant's Name _____ Phone # _____

Building Use:

One Family Two Family Multi-Family Condo Townhouse

Tower # _____ Apt. # _____

**** IMPORTANT MESSAGE ****

IF YOU ARE HOOKED TO A CENTRAL MONITORING SYSTEM, YOU MUST SHOW PROOF THAT THE ALARM SYSTEM IS IN PROPER WORKING ORDER. (COPY OF PAPERWORK FROM COMPANY)

The fee for inspection is \$50.00 for a SINGLE FAMILY RESIDENCE; \$75.00 for a TWO FAMILY RESIDENCE; \$100.00 for Three or more Families.

If the date of inspection is within four (4) days or less the fee is \$200.00.

Should the inspection fail or if the inspector must return for any reason, there is a \$40.00 RE-INSPECTION FEE.

Please mail or bring this form and a or check money order made payable to "TOWN OF SECAUCUS" to the Bureau of Fire Prevention, Municipal Government Center, Second Floor, Secaucus, NJ 07094

I HAVE READ AND UNDERSTAND ALL THE REQUIREMENT FOR THE REQUESTED INSPECTION _____

PARTY REQUESTING THE INSPECTION: _____

Owner: Realtor: Agent: Contact Number: _____

PLEASE NOTE: You will be contacted within 48 hours of receipt of your request by this office to schedule an inspection appointment. All inspections will be between the hours of 9:30 AM and 2:30 PM. **AN ADULT MUST BE AT THE RESIDENCE AT THE TIME OF THE INSPECTION – NO EXCEPTIONS.**

CLOSING DATE: _____

OFFICE USE ONLY Date: _____

Amount Paid _____ Check # _____ SD# _____

Date of Inspection ___/___/___ Date of re-inspection ___/___/___ Check # _____

§ 5:70-4.19 Smoke alarms for one- and two-family dwellings; carbon monoxide alarms; and portable fire extinguishers

- (a) In one- and two-family or attached single family dwellings subject to the requirements of N.J.A.C. 5:70-2.3, smoke alarms shall be installed as follows:
 - 1. On each level of the premises; and
 - 2. Outside of each separate sleeping area.
- (b) The smoke alarms required in (a) above shall be located and maintained in accordance with NFPA 72.
 - 1. The alarms shall not be required to be interconnected.
- (c) Ten-year sealed battery-powered single station smoke alarms shall be installed and shall be listed in accordance with ANSI/UL 217, incorporated herein by reference. However, A/C-powered single or multiple-station smoke alarms installed as part of the original construction or rehabilitation project shall not be replaced with battery-powered smoke alarms. The effective date of this subsection shall be January 1, 2019.
 - 1. A/C-powered smoke alarms shall be accepted as meeting the requirements of this section.
- (d) Carbon monoxide alarms shall be installed in all dwelling units in buildings in one- and two-family or attached single family dwellings, except for units in buildings that do not contain a fuel-burning device or have an attached garage, as follows:
 - 1. Single station carbon monoxide alarms shall be installed and maintained in the immediate vicinity of the sleeping area(s).
 - 2. Carbon monoxide alarms may be battery-operated, hard-wired or of the plug-in type and shall be listed and labeled in accordance with UL-2034 and shall be installed in accordance with the requirements of this section and NFPA-720.
- (e) A portable fire extinguisher shall be installed in accordance with the following:
 - 1. The extinguisher shall be within 10 feet of the kitchen and located in the path of egress;
 - 2. The extinguisher shall be readily accessible and not obstructed from view;
 - 3. The extinguisher shall be mounted using the manufacturer's hanging bracket so the operating instructions are clearly visible;
 - 4. The extinguisher shall be an approved listed and labeled type with a minimum rating of 2A-10B:C and no more than 10 pounds;
 - 5. The owner's manual or written operation instructions shall be provided during the inspection and left for the new occupant;
 - 6. The extinguisher shall be serviced and tagged by a certified Division of Fire Safety contractor within the past 12 months or the seller must have a receipt for a recently purchased extinguisher; and
 - 7. The top of the extinguisher shall not be more than five feet above the floor.
 - 8. Exception: Portable fire extinguishers shall not be required for seasonal summer units. For purposes of applying this exception, "seasonal summer unit" shall mean a dwelling unit rented for a term of not more than 125 consecutive days for residential purposes by a person having a permanent residence elsewhere, but shall not include use or rental of living quarters by migrant, temporary, or seasonal workers in connection with any work or place where work is being performed.